







产品型号	PT232161	
额定输入	1mA	2mA
额定输出	1mA	2mA
推荐负载	$\leq 200\Omega$	$\leq 200\Omega$
精度等级	0.1 / 0.2 (仅限比差)	
外形尺寸	 The technical drawing illustrates the physical dimensions of the PT232161 sensor. The top view shows a square component with a width of 19.5 and a height of 18.2. A central square area with a width of 14.0 and a height of 12.8 contains two red coils, each with four turns. The terminals are labeled 1, 2, 3, and 4, with asterisks indicating specific connection points. The side view shows a thickness of 4.0 and a mounting flange width of 0.8.	

产品型号	PT232361	
额定输入	1mA	2mA
额定输出	1mA	2mA
推荐负载	$\leq 200\Omega$	$\leq 500\Omega$
精度等级	0.1 / 0.2 (仅限比差)	
外形尺寸	 The technical drawing illustrates the physical dimensions of the PT232361 sensor. The front view (left) shows a square component with a width of 19.5 and a height of 18.9. Two mounting pins are located at the bottom, with a distance of 5 between their centers. The top view (right) shows the same square footprint with a width of 19.5 and a height of 17. The internal layout includes two coils, with terminals 1 and 2 on the left, and 3 and 4 on the right. The distance between the centerlines of the coils is 10. The distance from the top edge to the top of the coils is 12.8. The diameter of the mounting holes is indicated as $\varnothing 0.8$. Asterisks (*) mark the top corners of the internal square area.	

产品型号	PT232461	
额定输入	1mA	2mA
额定输出	1mA	2mA
推荐负载	$\leq 200\Omega$	$\leq 200\Omega$
精度等级	0.1 / 0.2 (仅限比差)	
外形尺寸	 The technical drawing illustrates the physical dimensions of the PT232461 sensor. The front view (left) shows a rectangular component with a width of 19.0 and a height of 18.2. It features two mounting pins at the base, each with a diameter of 0.8 and a height of 5.0. The side view (right) shows the component's profile with a width of 16.2, a total height of 10.0, and a mounting pin height of 7.2. Internal wiring is depicted in red, showing two coils connected to terminals 1, 2, 3, and 4, with asterisks indicating specific connection points.	

产品型号	PT232561	
额定输入	1 mA	2mA
额定输出	1 mA	2mA
推荐负载	$\leq 200\Omega$	$\leq 200\Omega$
精度等级	0.1 / 0.2 (仅限比差)	
外形尺寸		

产品型号	PT232661	
额定输入	1 mA	2mA
额定输出	1 mA	2mA
推荐负载	$\leq 200\Omega$	$\leq 200\Omega$
精度等级	0.1 / 0.2 (仅限比差)	
外形尺寸	 Technical drawing of the PT232661 sensor showing front and top views with dimensions. Front View Dimensions: - Overall width: 19 - Internal width: 17.5 - Overall height: 18 - Mounting hole diameter: 4-Ø0.6 - Bottom flange height: 3.5±0.2 Top View Dimensions: - Overall length: 15.24 - Internal length: 7.62 - Overall width: 10 - Terminal positions: 1, 2, 3, 4 - Star symbols (*) indicate specific features on the terminals.	

产品型号	PT232861	
额定输入	1mA	2mA
额定输出	1mA	2mA
推荐负载	$\leq 200\Omega$	$\leq 500\Omega$
精度等级	0.1 / 0.2 (仅限比差)	
外形尺寸	 The technical drawing consists of two views of the PT232861 sensor. The left view is a side profile showing a rectangular body with two mounting tabs on the sides. Dimensions include a total width of 10mm, a mounting tab width of 2.9±0.2mm, and a central body width of 14±0.2mm. The right view is a top-down perspective showing the sensor's footprint. It features two red coils labeled 1, 2, 3, and 4. Dimensions include a total width of 14±0.2mm, a total height of 16.5mm, a central coil area height of 12±0.2mm, and four mounting holes with a diameter of 4-Ø0.8mm. Asterisks (*) are placed near the coils.	