

A collection of black, C-shaped metal components, likely part of a magnetic core assembly, arranged in a stack. Each component has a green plastic piece attached to its outer edge.

- Large varieties, and wide current range.
- Two mounting methods, reliable and flexible.
- Flexible design, measurable and protective dual.
- High precision: the precision can reach 0.1 level
- High overload multiple, small signal output up to 12 times
- Strong versatility and good interchangeability

Technical drawing of a mechanical part, showing front and side views with dimensions.

Front View (Left):

- Overall height: H
- Height of the main body: $H1$
- Height of the base: $H2$
- Inner diameter of the central hole: \varnothing
- Small circular holes at the base corners.

Side View (Right):

- Overall width: W
- Width of the base: $W/2$
- Length of the main body: $D1$
- Overall length: L
- Internal features including a rectangular slot and a small component labeled $M1$.

MODEL NUMBER	TYPICAL SPECIFICATINOS		ACCURACY	OVER LOAD	DIMENSIONS						
					Ø	L	W	H/H1	D1	M1	H2
CT217103A	50A/20mA	RL=20Ω	0.1	1.2	30	76	25	83/67	69	5	6
	100A/50mA	RL=20Ω	0.1	1.2							
	200A/50mA	RL=20Ω	0.1	1.2							
CT217203A	100A/50mA	RL=20Ω	0.1	1.2	46	98	28	102/86	87	5	6
	200A/50mA	RL=20Ω	0.1	1.2							
	400A/200mA	RL=20Ω	0.1	1.2							
CT217303A	200A/50mA	RL=20Ω	0.1	1.2	65	124	28	118/105	110	6	6
	400A/200mA	RL=20Ω	0.1	1.2							
	600A/200mA	RL=20Ω	0.1	1.2							
CT217403A	200A/50mA	RL=20Ω	0.1	1.2	80	140	32	140/130	122	6	8
	500A/200mA	RL=20Ω	0.1	1.2							
	1000A/1A	RL=5Ω	0.5	1.2							
CT217503A	500A/1A	RL=5Ω	0.5	1.2	100	167	32	156/148	153	6	8
	1000A/1A	RL=5Ω	0.5	1.2							
	1500A/1A	RL=5Ω	0.5	1.2							
CT217603A	1000A/1A	RL=5Ω	0.5	1.2	120	188	32	175/172	170	6	8
	1500A/1A	RL=5Ω	0.5	1.2							
	3000A/1A	RL=20Ω	0.5	1.2							
CT217703A	1500A/1A	RL=20Ω	0.5	1.2	150	225	32	208/206	205	6	10
	3000A/1A	RL=20Ω	0.5	1.2							
	4000A/1A	RL=20Ω	0.5	1.2							
CT217803A	2000A/1A	RL=20Ω	0.5	1.2	200	296	40	270/274	278	6	12
	4000A/1A	RL=20Ω	0.5	1.2							
	6000A/1A	RL=20Ω	0.5	1.2							